

For light applications around your home

- recommended for:
- garden paths
  - wood yards / storage areas
  - dumping grounds



Specifications	
Dimensions:	33 x 33 x 3 cm   12.99 x 12.99 x 1.18"
Wall thickness:	up to 4.4 mm   0.17"
Dimensional stability:	-50° / 90° C   -58° / 194° F
Solubility:	resistant to acids, alkalis, alcohol, oil and petrol (de-icing salt, ammonia, acid rain, etc.)
Moisture absorption:	0.01 %
Weight per m²   10.76 ft²	5.31 kg   11.71 lbs
Weight per piece:	0.59 kg   1.3 lbs
Interlock:	36 notched connectors per m²
Max. open surface:	approx. 80 %
Material:	LD-PE, recycled
Loadability:	up to 800 t/m² (depending on fill type)
Compressive strength:	up to 20 t point axle load (DIN 1072)
UV-resistant and weatherproof:	according to DIN EN ISO 4892-2 and DIN EN 60068-2-5
Environmental compatibility:	environmentally neutral according to OECD 202:2004
Highly durable:	according to DIN EN 124:2011 (D400)
Tensile strength:	> 5 kN/m
Package	
Standard installation unit:	1 layer (= 12 pieces, equates 1.33 m²)
Layer per pallet:	71
Area per pallet:	94.66 m²   1 018.91 ft²
Qty. per pallet:	852
Dimensions:	105 x 135 x 229 cm   41.34 x 53.15 x 90.16"
Weight per pallet:	512 kg   1 128.77 lbs (incl. plastic pallet and packaging)



NOTE:

- a. Please note the installation instructions on our website!  
Subject to change without prior notice. E. & O.E.
- b. The listed details are nominal dimensions and subject to a certain tolerance due to material changes

Your contact:



**INTERNATIONAL TRADING COMPANY**

**+31 652 567 701**

**INFO@MACCROX.COM**